

PINMIC™



Introducing the RØDE PINMIC™

Whether you're presenting for television or live on-stage, in a 20,000 seat auditorium or in a house of worship, RØDE has your needs covered with the intuitive and subtle PinMic™.

Featuring innovative, industry-leading design, the RØDE PinMic™ is the first of its kind. The pin-on placement of the microphone provides an ultra discreet appearance, while also simplifying cable management.

The included mini-furry for high wind protection ensures quality recordings in adverse environments, while the anti-trauma water resistant case provides rugged and secure protection for the microphone, cable and accessories.

Knowing that versatility is paramount in any product, we at RØDE have developed the MiCon™ connector system which provides seamless integration between the PinMic™ and a wide range of wireless systems.



PINMIC™

INTUITIVE AND SUBTLE

- Ultra discreet appearance
- Lightweight and easy to position
- Pins through clothing up to approximately 1.5mm (0.006") thick (standard model) or approximately 1.5 ~ 3.5mm (0.006 ~ 0.14") thick (heavy duty model)
- Removable mesh head

HIGH QUALITY PERFORMANCE

- Low noise miniature microphone capsule
- Low handling noise

UNIVERSAL COMPATIBILITY

- RØDE MiCon™ interconnectivity system provides seamless integration with a wide range of wireless systems while maintaining discreet and unobtrusive appearance

ACCESSORIES

- Supplementary mesh head (silver) suitable for spray paint customisation to fully match clothing
- Anti-trauma water resistant storage case
- Mini-furry for high wind protection
- Shielded Kevlar® reinforced cable with moulded backplate
- Lapel-style cable management clip
- Adjustment tools
- Sanitary cleansing wipes

Compact, interchangeable MiCon™ adaptors available to suit industry standard wireless systems*

SPECIFICATIONS

Acoustic Principle	Permanently Polarised Condenser
Directional Pattern	Omni-directional (see graph)
Frequency Range	60 Hz ~ 18 KHz (see graph)
Output Impedance	3k Ω Typical
Signal To Noise Ratio	69 dBA
Equivalent Noise	25 dB SPL (per IEC651)
Clipping SPL	110 dB
Maximum Output	189 mV**
Sensitivity	-33.5 dB re 1 V/Pa (21 mV @ 94 dB SPL) ± 3 dB @ 1 kHz
Dynamic Range	85 dB Typical**
Power Requirements	Min 2 V ~Max 5 V through RØDE wireless adaptors P48 through RØDE XLR adaptor
Output Connection	RØDE MiCon™ connector

** Calculated from maximum SPL peak before clipping

All measurements are calculated when powered at 5 V or P48 (RØDE XLR adaptor)

*MiCon™ adaptors sold separately - see rodemic.com/pinmic for a full list of compatibility

