

MD 441 U

Microphones | Dynamic Microphone

Cat. No. 000762

General Description

The MD 441 U is a microphone of exceptional quality: its acoustic properties come as close as possible to those of a condenser microphone. Accurate signal response and low distortion are ensured, even with the highest sound pressure levels. Surface: all metal body with black leatherette finish, sound inlet basket: nickel plated.



Cable pictured is an accessory not supplied with the microphone

Features

- Excellent feedback rejection
- Excellent sound quality
- Spring capsule mounting provides low sensitivity to handling noise
- Hum compensating coil
- Five position bass roll-off switch
- Brilliance (treble boost) switch
- Integral pop filter
- Delivery includes: 1 MD 441 U


1 microphone clamp MZA 441


Recommended Accessories

■ MZT 100 table stand	Cat. No. 001883
■ MZT 441 table stand	Cat. No. 000799
■ MZT 14 mounting bolt	Cat. No. 001895
MZW 40 foam windshield	Cat. No. 001794
MZW 441 foam windshield	Cat. No. 000976

Technical Data

Pick-up pattern	super-cardioid
Frequency response	30 – 20,000 Hz
Sensitivity (free field, no load, 1 kHz)	1.8 mV/Pa ± 2 dB
Nominal impedance	200 Ω
Min. terminating impedance	1 kΩ
Dimensions	270 x 33 x 36 mm
Weight	approx. 450 g





Profile

Super-cardioid studio microphone, hum compensating coil, five position bass control, brilliance switch, integral pop filter, frequency response 30 – 20,000 Hz, sensitivity (free field, no load) 1.8 mV/Pa \pm 2 dB at 1 kHz, nominal impedance 200 $\Omega_{\rm r}$, min. terminating impedance 1 k $\Omega_{\rm r}$, dimensions 270 x 33 x 36 mm, weight approx. 450 g.