


## Specifications

GENERAL SPECIFICATIONS		
Power	DC12V (AC adapter), DC7.4V (Battery)	
Power consumption	Approx. 12 W (with VF in REC mode, default setting)	
Dimensions	177.5 mm (W) x 197 mm (H) x 415.5 mm (D)	
Weight	approx. 2.5 kg (including battery)	
Operation temperature	0°C to 40°C (32°F to 104°F)	
Storage temperature	-20°C to 50°C (14°F to 122°F)	
Operating humidity	30% to 80%	
Storage humidity	under 85%	
CAMERA		
Image sensor	1/3" CMOS 2.5M pixels	
Synchronizing	Internal synchronization	
Stabilizer	Optical image stabilizer	
Lens	F1.6 (wide) to F3.0 (Tele) f=4.1mm to 94.3mm (f=29 mm to 667mm (35mm equivalent))	
Filter diameter	72mm	
Shutter speed	1/6 ~ 1/10000, EEI	
Gain	(-6, -3: Extended mode only), 0, 3, 6, 9, 12, 15, 18, 21, 24 dB, Lolux (30, 36 dB), AGC	
ND filter	none, 1/4, 1/16, 1/64	
LCD display	3.5-inch 920 k pixels, 16:9	
Viewfinder	0.45-inch 1.22 M pixel, 16:9	
VIDEO/AUDIO RECORDING		
Recording media	2x SDHC/SDXC memory card (HD: Class 6/10 AVCHD/SD/Web: Class4)	
Video recording	Video codec	MPEG-4 AVC/H.264 (HD/SD), MPEG-2 Long GOP VBR (HD) MPEG-2 Long GOP CBR (HD), AVCHD (HD/SD)
	File format	MOV, MP4, MTS (AVCHD), MXF
	HD (MPEG-2 Long GOP VBR)	NTSC setting: HQ mode: 1920 x 1080/59.94i, 29.97p, 23.98p, 1440 x 1080/59.94i 1280 x 720/59.94p, 29.97p, 23.98p (Max 35Mbps)
		PAL setting: HQ mode: 1920 x 1080/50i, 25p, 1440x1080/50i 1280 x 720/50i, 25p (Max 35Mbps)
	HD (MPEG-2 Long GOP CBR)	NTSC setting: SP mode: 1440x1080/59.94i, 1280x720/59.94p (18.3Mbps)
		PAL setting: SP mode: 1440x1080/50i, 1280x720/50p (18.3Mbps)
	HD (H.264)	NTSC setting: XHQ mode: 1920x1080/59.94p, 59.94i, 29.97p, 23.98p (Max 50Mbps) 1920x1080/59.94i, 29.97p, 23.98p (Max 35Mbps)
		PAL setting: XHQ mode: 1920 x 1080/50p, 50i, 25p (Max 50Mbps) 1920 x 1080/50i, 25p (Max 35Mbps)
	AVCHD	NTSC setting: Progressive mode (Max 28Mbps): 1920 x 1080/59.94p HQ mode (Max 24Mbps): 1920 x 1080/59.94i, SP mode (Max 18Mbps): 1920 x 1080/59.94i LP mode (9Mbps): 1440 x 1080/59.94i, EP mode (5Mbps): 1440 x 1080/59.94i
		PAL setting: Progressive mode (Max 28Mbps): 1920 x 1080/50p HQ mode (Max 24Mbps): 1920 x 1080/50i, SP mode (Max 18Mbps): 1920 x 1080/50i LP mode (9Mbps): 1440 x 1080/50i, EP mode (5Mbps): 1440 x 1080/50i
SD (H.264)	NTSC setting: 720 x 480/59.94i (GY-HM660U) PAL setting: 720 x 576/50i (GY-HM660E/GY-HM660EC)	
Proxy (H.264)	NTSC setting: HQ mode (3Mbps): 960 x 540/29.97p, 23.98p, LP mode (1.2Mbps) 480 x 270/29.97p, 23.98p	
	PAL setting: HQ mode (3Mbps): 960 x 540/25p, LP mode (1.2Mbps): 480 x 270/25p	
Audio recording	LPCM 2ch, 48kHz/16-bit (MOV/MP4), Dolby Digital, 2ch (AVCHD), $\mu$ Law 2ch (Proxy)	
INTERFACE		
Video output	AV output ( $\phi$ 3.5mm mini jack x1)	
	SDI output (BNC x1)	
	HDMI output x1	
Audio input	XLR x2 (MIC,+48V/LINE), $\phi$ 3.5mm mini jack x1	
Audio output	AV output ( $\phi$ 3.5mm mini jack x1)	
Headphone	$\phi$ 3.5mm mini jack x1	
Remote	$\phi$ 2.5mm mini jack x1	
Time code link input/output	RCA x1	
USB	HOST x1 (Network Connection), DEVICE x1 (Mass storage)	
PROVIDED ACCESSORIES		
Battery (SSL-JVC50) x1, AC Adapter x1		

## Dimensions

Unit: inches (mm)



Apple, Apple logo, Macintosh, QuickTime, and Final Cut Pro are trademarks of Apple Inc. registered in the United States and other countries.

"AVCHD Progressive/AVCHD" and the "AVCHD Progressive/AVCHD" logo are trademarks of Panasonic Corporation and Sony Corporation.

Dolby is a registered trademark of Dolby Laboratories. The SD, SDHC and SDXC logos are trademarks of the SD Card Association. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Product and company names mentioned here are trademarks or registered trademarks of their respective owners. All screen pictures in this brochure are simulated.

Simulated pictures.

The values for weight and dimensions are approximate.

E.&O.E. Design and specifications subject to change without notice.

# JVC

HD/SD Memory Card Camcorder

# GY-HM660



## Breaking News, Breathtaking Views.

# JVCKENWOOD

DISTRIBUTED BY

# ProHD



Shown with optional microphone.

# Live Streaming from Virtually Anywhere in the World.

Newsworthy things are happening all the time, so deliver it as it happens with the IP connectivity and live streaming capability of JVC's GY-HM660. And to make sure you can tell it as it is, this high quality camera captures a high quality bright image with F12 (60Hz)/F13 (50Hz) sensitivity.

## High Quality Live Streaming up to 12Mbps

Real-time Full HD live streaming via 4G LTE/3G, Wi-Fi, and Ethernet up to 12Mbps.

## Advanced IP Connectivity

Support various IP connectivity and IP functions, providing immediate delivery for ENG applications.

## F12 (60Hz)/F13 (50Hz) Sensitivity

New 3CMOS sensors enable extreme high sensitivity and low noise which strongly support ENG shooting.

## SMPTE 2022-1 Protocol

Newly supported SMPTE 2022-1 protocol enables simple error correction for high quality streaming.

## Quick Footage Transfer via FTP Server

Footage can be transferred from the camera while recording to an FTP server.

## Built-in Zixi Engine

Advanced live streaming with FEC and ARQ over 4G LTE or a standard Internet connection can be achieved with built-in Zixi technology.

## IP Remote Control

Remote control via wireless/wired LAN supported from smart devices and PCs to control the GY-HM660 with screen viewing.

## 50Mbps H.264 & MPEG2, AVCHD Support

The GY-HM660 supports various video formats and codecs required for just about any workflow.

## Combination Rec with Dual CODEC

Recording to two SDHC/SDXC cards in same/different formats enable reliable backup and flexible utility with IP functions.



## 23x Zoom Lens and 3 isolated Manual Rings

High-quality optical 23x Zoom lens and 3 manual rings are tuned up for camera crews.



# Camera Features



## Newly developed 1/3-inch 3CMOS Sensor (1920 x 1080) boasts Sensitivity of F12/F13 (60/50Hz)

At the heart of the GY-HM660 are three, newly developed 1/3-inch CMOS sensors with 2.5M pixels, each capable of capturing full HD 1920 x 1080 resolution images. Featuring 12-bit processing, an excellent sensitivity of F12 (60Hz) /F13 (50Hz) at 2000 lux, and a remarkable signal-to-noise ratio, the devices provide superior precision and color reproduction with minimal aberration. For improved CMOS sensor performance, flash-band compensation is also supported.



Compare the image brightness between sensitivity of F5.6 (left) of a conventional camera and F12 (60Hz) at 2000 lux on the GY-HM660.

## Revolutionary FALCONBRID™ Image Processing Engine

FALCONBRID™ is JVC's high-speed processor for advanced video applications. Delivering tremendous processing power on a single chip, the on-board engine is capable of processing large amounts of video data at exceptional speeds. The combination of FALCONBRID™ engine, 2D DNR processing & compensation circuitry, and wide dynamic range achieve superior image quality. The GY-HM660 is equipped with two FALCONBRID™ engines, which enable parallel processing like recording at two formats (HD + SD and HD + Web) or Live Streaming while Recording.



FALCONBRID™

## Various Codecs and File Formats including the Original H.264 XHQ (50Mbps) mode

FALCONBRID™ engine is capable of supporting major file formats such as .MXF with rich metadata optimized for asset management, .MOV with Apple Final Cut Pro, .MP4 of XDCAM EX™ cameras, and .MTS for AVCHD compatibility, as well as high-definition images in MPEG-2 35Mbps (HQ) and AVCHD 28Mbps (Progressive) format.

Furthermore, the processor also supports H.264 video format in 50Mbps extreme high quality (XHQ) mode for virtually no block noise and to capture high-speed moving subjects all the way to Web LP (480 x 270) mode (Web <Proxy>) suitable for internet applications. Using the camera's Dual recording capability, different combinations of HD+SD and HD+Web are also supported.

Video format	MPEG-2			AVCHD					H.264				
	HQ (35Mbps)	SP (25Mbps)	SP (19Mbps)	Progressive (28Mbps)	HQ (24Mbps)	SP (18Mbps)	LP (9Mbps)	EP (5Mbps)	XHQ (50Mbps)	UHQ (35Mbps)	SD (8Mbps)	Web HQ (3Mbps)	Web LP (1.2Mbps)
Mode (Bit rate)	MOV/MP4/MXF			MTS					MOV				
File format	Linear PCM 2ch			AC3 2ch					Linear PCM 2ch				
Audio format	60i/50i/30p/25p/24p			60p/50p					60i/50i				
HD	1920 x 1080	60i/50i/30p/25p/24p		60p/50p	60i/50i	60i/50i			60p/60i/50p/50i/30p/25p/24p	60i/50i/30p/25p/24p			
	1440 x 1080	60i/50i	60i/50i			60i/50i	60i/50i						
	1280 x 720	60i/50i/30p/25p/24p <sup>*1</sup>		60p/50p									
SD	720 x 480									60i <sup>2</sup> /50i <sup>3</sup>			
PROXY	950 x 540										30p/25p/24p		
	480 x 270											30p/25p/24p	

\*1: Only with MOV/M4 file formats \*2: U only \*3: E only

## 23x Fujinon Auto Focus Zoom Lens with Manual Functions


The GY-HM660 is equipped with the Fujinon wide angle 23x optical zoom lens to offer sufficient magnification for shooting. Delivering superior low-light performance and ensuring brightness at the tele end, the lens offers F1.6-3.0, a focal range of 29mm-667mm

(35mm equivalent) and includes servo zoom, manual focus, and iris rings, along with a four-position (clear, 1/4, 1/16 and 1/64) ND filter. Other features include an optical image stabilizer and chromatic aberration correction.

23x Zoom Lens




Focus, zoom and iris rings are isolated and ergonomically aligned with buttons offering intuitive, stress-free operations.




23x zoom lens, sufficient magnification for shooting, at Wide end (left) on to Tele end (right).

## Upgraded High-resolution 920K Pixels 3.5-inch LCD Display with Focus Assist and various GUI


The high-resolution 920K pixels 3.5-inch LCD monitor provides a wide aspect ratio of 16:9 with a wide array of monitoring and setup indications. Since the LCD is top-mounted, not only is it ideal for shooting at various angles but also provides ample distance from the cameraman's eyes to the LCD to achieve better visibility in handheld camera applications. It also features a Focus Assist function that highlights the edges of objects shown in the viewfinder in color (red, green or blue) to help the cameraman stay focused on the action.



When the Focus Assist function is set to ON, objects that are in focus appear with colored edges (selectable from red, green or blue) as seen here.



Audio equalizer




Color matrix adjustment


## Dual SDHC/SDXC Card Slots for Maximum Versatility

Dual SDHC/SDXC card slots make the GY-HM660 a truly versatile camcorder, offering such benefits as series recording, dual recording, and backup recording modes with reliable and cost-effective media.

• **Series (relay) recording mode:** Shoot continuously and seamlessly over multiple cards. When one card is full, the camcorder switches seamlessly and automatically to the other card. And because cards are hot swappable, there is in effect no limit to the continuous shooting time in any mode, even with lower capacity cards. It is possible to start editing footage from one card while still shooting to the other.




• **Dual (simultaneous) recording mode (HD/HD, HD/SD or HD/Web):** Easily create duplicate backup files as you shoot—either to divide editing tasks or simply for peace of mind. With the new dual codec, it is now possible to record full HD files on one memory card while simultaneously creating smaller SD or proxy files on the other, providing the flexibility for a range of workflow possibilities.



• **Backup recording mode:** While the Rec trigger is used to REC and STOP recording on one card, the other card can act as a continuous backup that overrides the pause function.\* This is a unique mode highly demanded by theatrical and bridal camera crew.

\*During simultaneous backup recording in HD mode, the duplicate file records in the same file format and bit rate as the original.



## Cutting-edge Connectivity including SDI (HD/SD) Out

Equipped with leading edge connections, the GY-HM660 offers versatility while meeting the needs of professional applications. For easy monitoring of footage, you can monitor from the digital SDI and HDMI outputs simultaneously, easily switching between output in HD or SD.

- SDI (HD/SD) out
- HDMI (HD/SD) out (60p support)
- TC Sync in/out
- AV out
- USB (Host x1, Device x1)
- XLR 3-pin x2 (MIC, +48V <phantom power>, LINE)
- Aux in for Wireless Receiver
- ø2.5mm Remote Control
- ø3.5mm Stereo Headphone out



# IP Network & Live Streaming



## Live Streaming up to 12Mbps of High Bit Rate Streaming

If your task involves mission-critical ENG applications, turn to the GY-HM660 as it is capable of streaming LIVE HD/SD and proxy video/audio files via network up to 12Mbps. Coupled with the superior mobility of the camera, this wireless capability allows you to stream backhaul live

to the newsroom or to a reliable cloud service such as Zixi, as well as content delivery networks such as USTREAM and YouTube using Wi-Fi or 4G-LTE network. All you need to do is press a button and you're streaming HD to the world.

## IP Connection Realized with a Variety of USB Host Adapters

Full HD video footage recorded on the GY-HM660 can stream backhaul live to the target location using an adapter such as 4G LTE/3G modem, Wi-Fi LAN, or Ethernet, whichever is more stable and cost-effective. Such use of an adapter enables uploading video clips to and receiving

Metadata (in XML) from the FTP server, remote controlling web server content, viewing and editing Metadata, and most of all for live streaming footage from anywhere in the world immediately after it is recorded.

## Advanced IP Functions for FTP Uploading

Video clips recorded on an SDHC/SDXC card can be transferred from the GY-HM660 via FTP server. Clips can be trimmed right on the camera, which is useful for selecting only vital scenes before uploading to an FTP

server. What's more, if an upload is interrupted by a weak connection, the FTP Resume function is smart enough to restart from where it left off. This will help to save time for uploading.

## Supports SMPTE 2022-1 Protocol for HQ Streaming

Stable, high-quality live streaming over IP is made possible thanks to support for the new SMPTE 2022 protocol. Since its introduction in 2007, the SMPTE 2022 standard has added sections to cover more

types of IP video transport. Of the standard, the GY-HM660 supports the first protocol, which is forward error correction (FEC) for real-time video/audio transport over IP networks.

## Advanced Live Streaming with Built-in Zixi Engine

For advanced live streaming solutions, JVC has teamed with Zixi. The GY-HM660 features the Zixi engine, installed directly into the camera to provide high-quality delivery over 4G LTE or standard Internet connection. The powerful Zixi engine applies forward error correction (FEC) and adaptive bit rate control with the new "high reliable mode"

to correct packet loss by over 40%\*, delivering a robust, reliable HD stream. In the camera's FTP setting, the new Zixi protocol has been added for transferring clips while recording from the camera via Zixi server.

\*Quality of Live streaming depends on network conditions including packet loss.

## IP Remote Control with Viewing

When the camera is IP connected to a server console, vital camera operations can be remotely controlled via wireless or wired LAN from smart devices and computers. Remote control functions include lens and camera settings as well as registering zoom presets. Best of all, recording and live streaming may also be triggered remotely—invaluable for minor adjustments when a single reporter is operating the camera or shooting with a 2-camera setup.




The camera on the stage can be remote controlled from a smart device. Controls include REC/STOP, Zoom, Focus, Iris and more detailed settings while viewing live images from the smart device screen.

## IFB Return Audio via IP\*

With Interruptible FeedBack (IFB) return audio function\*\*, the camera crew can listen to audio from remote locations via IP even while live streaming. The same audio can be heard from multiple GY-HM660 cameras simultaneously.

\*Future update \*\*Requires other devices



## Optional Accessories

**SSL-JVC50**  
Standard Li-ion Battery (IDX)  
DC7.4V, 4900mAh, 37Wh



**SSL-JVC75**  
Long-life Li-ion Battery with D-TAP Connector (IDX)  
DC7.4V, 7350mAh, 55Wh



**LC-2J**  
7.4V 2-ch Simultaneous Charger (IDX)



## SDHC Class 4/6/10, SDXC recording time (approx.)

Recorded files can be divided while recording MOV/MXF on an SDXC card. User can select recording capacity/ time between "up to 4GB/30 minutes max" and "up to 64GB/4 hours max".

	MOV/MP4/MXF				MTS				MOV				
	MPEG-2/HD		HQ Progressive	1080p	AVCHD		EP	H.264/HD		H.264/SD			
	HQ	SP			HQ	LP		XHQ	UHQ	SD	HQ	LP	
	720p/1080i	1080i	720p		1080i			1080p			480i	540p	270p
<b>4GB</b>	12m	17m	22m	16m	19m	25m	46m	1h 22m	9m	17m	47m	2h 10m	4h 45m
<b>8GB</b>	25m	35m	45m	33m	38m	50m	1h 35m	2h 48m	18m	35m	1h 35m	4h 30m	9h 40m
<b>16GB</b>	50m	1h 10m	1h 30m	1h 7m	1h 18m	1h 40m	3h 10m	5h 36m	36m	1h 35m	3h 10m	9h	19h 20m
<b>32GB</b>	1h 40m	2h 20m	3h	2h 15m	2h 36m	3h 20m	6h 20m	11h 12m	1h 12m	2h 20m	6h 20m	18h	19h 20m
<b>64GB</b>	3h 20m	4h 40m	6h	4h 30m	5h 12m	6h 40m	12h 40m	22h 24m	2h 25m	4h 40m	12h 40m	36h	78h 40m
<b>120GB</b>	6h 40m	9h 20m	12h	9h	10h 32m	13h 20m	25h 20m	44h 48m	4h 50m	9h 20m	25h 20m	72h	157h 20m

Notes: • Recording times are estimate. • Recommended SDHC/SDXC memory card brands: Panasonic, Toshiba, and SanDisk  
• SDHC Class 10 enabled only in XHQ mode; SDHC Class 4 enabled in AVCHD mode.