

Lightweight Supports for 2/3" Chip cameras.



Weight savings up to 80%
with carbon fibre rods.



V-connection



Adaptor cable
401-CABLE



U-clamp
401-70

Accessories:	Article no.
Rod adapter (notch for cable)	401-70
Cable with Hirose 12-pin angle plug for Fujinon lens	401-cable
1 Pair rod extensions 190 mm with thread mount	401-83-190
1 Pair rod extensions 100 mm with thread mount	401-83
1 Pair rod extensions 50 mm with thread mount	401-14

Support system for the 15mm standard - for MatteBoxes, lens supports, follow focus devices, fluid-zoom drives, wireless focus receivers and motors.

The light-weight supports are equipped with rod holder for height and lateral adjustment. The base plate is made of hardened aluminium. The V-shaped connection on the bottom is compatible with the tripod adapters supplied by the camera manufacturer. The high-strength aluminium rods correspond to the 15 mm standard (rod diameter 15mm, rod centre-to-centre spacing 60 mm) and have a length of 205 mm. As an option **super lightweight carbon fibre rods** are available.

The patented QuickLock plate (see Page 25) offers a particularly stable connection to the tripod for quick and easy change between shoulder and tripod. See page 23 for special light-weight supports (HD) to use with hand

Components:	Article no.
Lightweight support:	
Sony Universal	401-50
for Sony BVP-550P	401-85
Panasonic Universal	401-89B
for JVC GY-HM 700 (rod length 150mm)	401-63
for JVC GY-HD 250 / 251 (rod length 150mm)	401-65
for JVC GY-500 / DY-90E	401-68
for JVC GY-700DV / GY-5000	401-69
for Thomson TTV 1657	401-84
Ikegami Universal	401-77
for Ikegami HK 399	401-80
for Ikegami types DNS 33 / HDNX 10 among others	401-66A
for BTS LDK 100 / 120 / 6000 / 7000 and other	401-91
Rods Ø 15 mm (spare parts and optional carbon fibre rods):	
Aluminum-Rod, length 205mm (standard length)	401-01-04
1 Pair Carbon-Fibre-Rods , length 205mm (standard length)	401-01CF
1 Pair Carbon-Fibre-Rod Extensions , length 100mm	401-83CF
1 Pair Carbon-Fibre-Rod Extensions , length 50mm	401-14CF
Aluminum-Rod, length 114	401-01-04-114
Aluminum-Rod, length 128	401-01-04-128
Aluminum-Rod, length 150	401-01-04-150
Aluminum-Rod, length 205 with notch	401-01-04A
Aluminum-Rod, length shorter than 205 mm, customized	401-01-06