

# DeckLink Mini Recorder



Record uncompressed 10-bit video from SDI and HDMI video sources. DeckLink Mini Recorder switches between SD and HD video formats and is perfect for building ingest servers or other video solutions where you need to capture only in a low profile card! Includes two PCIe shields for both full height and low profile slots.

\$145

# Connections

# **SDI Video Input**

1 x 10-bit SD/HD switchable

#### **HDMI Video Input**

1 x HDMI type A connector.

#### **SDI Audio Input**


8 channels embedded in SD and HD.

#### **HDMI Audio Input**

8 Channels embedded in SD and HD.

#### Computer Interface

PCI Express 1 lane, compatible with 1, 4, 8 and 16 lane PCIe slots.



# Codecs

Supports: AVC-Intra, AVCHD, Canon XF MPEG2, Digital SLR, DV-NTSC, DV-PAL, DVCPRO50, DVCPROHD, DPX, HDV, XDCAM EX, XDCAM HD, XDCAM HD422, Apple ProRes 4444, Apple ProRes 422 HQ, Apple ProRes 422, Apple ProRes LT, Apple ProRes 422 Proxy, Uncompressed 8-bit 4:2:2, Uncompressed 10-bit 4:2:2.

## Software

#### **Software Included**

Media Express, Disk Speed Test, LiveKey, Blackmagic System Preferences and Blackmagic driver on Mac OS X. Media Express, Disk Speed Test, LiveKey, Blackmagic Control Panel and Blackmagic driver on Windows 7 or Windows 8. Media Express, Blackmagic Control Panel and Blackmagic driver on Linux.

#### Internal Software Upgrade

Firmware built into software driver. Loaded at system start or via updater software.

#### **Physical Installation**

PCI Express 1 lane, compatible with 1, 4, 8 and 16 lane PCI Express slots on Mac OS X, Windows 8 and Linux. Mac OS X systems require a Mac Pro computer. Please check the Support pages to see the full system requirements.

## Software Applications



DaVinci Resolve



Eusion



Premiere Pro CC Avid Media



Avid Media Composer



After Effects CC



Avid Pro Tools



Steinberg Cubase



Steinberg Nuendo



Photoshop CC



Media Express

Other supported applications include: Nuke, Avid Symphony, Avid News Cutter, Tools On Air just:in & live:cut & just:play & just:live, Softron OnTheAir, MovieRecorder and OnTheAir CG, Flash Media Live Encoder, Wirecast, Livestream Procaster, Resolume Avenue 4, Sony Vegas Pro, Corel VideoStudio Pro X4, CyberLink Power Director, MAGIX Video Pro X4, Vidblaster Pro & Studio & Broadcast, Uniplay, Playbox AirBox, CasparCG, Magicsoft CG, Xsplit Broadcaster, Imagine Communications Velocity & InfoCaster.

## Video Standards

## **SD Format Support**

525i29.97 NTSC, 625i25 PAL

#### **HD Format Support**

720p50, 720p59.94, 720p60 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30 1080PsF23.98, 1080PsF24, 1080PsF25, 1080PsF29.97, 1080PsF30 1080i50, 1080i59.94, 1080i60

#### **SDI Compliance**

SMPTE 259M and 292M.

#### **SDI Metadata Support**

VITC read for 3:2 pulldown removal. VANC capture using up to 3 lines of video in file. HD RP188 and closed captioning.

## **Audio Sampling**

Television standard sample rate of 48 kHz and 24 bit.

## **Video Sampling**

4:2:2

## **Color Precision**

10-bit

## **Color Space**

REC 601, REC 709

#### **HDMI Configuration**

HDMI automatically configures to connected display.

### **HDMI** Resolution

Pixel for pixel HD resolution input to connected device.

#### **HDMI Color Precision**

10-bit

## **Multiple Rate support**

SDI and HDMI are switchable between standard definition and high definition.

## **Copy Protection**

HDMI input is unable to capture from copy protected HDMI sources. Always confirm copyright ownership before capture or distribution of content.

## Processing

#### **Colorspace Conversion**

Hardware based real time.

## **HD Up Conversion**

Software based up conversion during video capture.

# **Operating Systems**



Mac OS X 10.9 Mavericks, Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan or later.



Windows 8.1 or Windows 10.



Linux

# **EMC Certifications**

FCC, CE and C-Tick

# Physical Specifications





# **Environmental Specifications**

Operating Temperature 5° to 40° C (32° to 104° F)

Storage Temperature -20° to 45° C (-4° to 113° F) Relative Humidity 0% to 90% non-condensing

## What's Included

DeckLink Mini Recorder Low profile slot bracket SD card with software and manual

# Warranty

3 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2016, all rights reserved.

All trademarks are property of their respective owners. MSRP excludes sales taxes/duties and shipping costs.

Blackmagic Design Authorized Reseller