

Remote Operation Panel (ROP)

AK-HRP1000

Remote Operation Panel (ROP)



KEY FEATURES

- 1/4-type rack size remote operation panel
- Colour LCD readout display allows GUI operation, and also supports PoE+ and IP control
- Variable master gain, colour temperature and master flare can all be assigned to a user knob
- Joystick control lever allows Iris/Pedestal operation
- Can be used with a mix of studio and Panasonic remote control cameras via IP connection

1/4-type rack size remote operation panel which supports PoE+ and IP control

SPECIFICATIONS

Power Supply	12 V DC (Power supply from camera: 10 V - 16 V DC) 42 V - 57 V DC (PoE power supply)
Power Consumption	0.51 A (Power supply from camera: 10 V - 16 V DC) 0.15 A (PoE power supply)
Operating Temperature	0°C to 40°C (32°F to 104°F)
Humidity	90% or less
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Weight	Approx. 1.7 kg (3.75 lb)
Dimensions (W x H x D)	102 mm x 385 mm x 113 mm (4 inches x 15-3/16 inches x 4-7/16 inches)
Camera/CCU Control	Control signals (camera, CCU control) Power supply 16 V DC (when CCU connected)*4, 12 V DC (when camera connected)*4
Maximum Cable Length	When camera connected: 20 m (65.7 ft) When CCU connected: 50 m (164 ft)
Note	*1: Depending on the setting, only one of them can be selected at one time. *2: The BB (black burst) signal and tri-level sync signal of the reference input are recognized automatically. *3: IP video cannot be transmitted when [CCU MODE] is set to [2160/23.98p], [2160/23.98PsF], [1080/23.98p], or [1080/23.98PsF]. *4: Can be provided from CCU
Compatibility	-

URL: https://business.panasonic.co.uk/professional-camera/Remote_Operation_Panel/ak-hrp1000

CONTACT

Web: <https://business.panasonic.co.uk/professional-camera/contact-us>