

PIERRE BOUDARD FOUNDER

POWER SOLUTIONS

- I For Camcorders from DSLR to Digital Cinematography
- I 15 Years of Experience in Powering Production Equipment
- I Using High-End Sanyo Cells exclusively



WWW.BEBOB.TV



UNIQUE FEATURES

VIRTUALLY UNBREAKABLE

I The bebob batteries are designed to survive a fall of 1.5 m.

Nevertheless, if one should crack, the modular concept allows any mechanical part to be replaced. Each is covered by a 2-year warranty.



RE-CELLABLE

I The bebob batteries aren't disposables but durable equipment. When the capacity has become insufficient after years of use, batteries can be re-celled easily in our factory for about half the price of a new one or even for free if it happens during the warranty period.



TWIST-D-TAP

I Only bebob batteries offer the unique bebob Twist-D-Tap. This rainproof socket allows you to plug a D-Tap connector into the battery with your choice of cable trailing from the left or right.



TWO DIFFERENT MOUNTS

THROUGHOUT ALL POWER SOLUTIONS

- I All products are available either as V-Mount (compatible with Sony, IDX, etc.) or as 3-Stud Snap-on (compatible with Anton Bauer, etc.).
- I The different mounts are indicated in the product names: »V« stands for a V-Mount, and »A« stands for a 3-Stud Snap-on.









COCO BATTERY ADAPTERS

TECHNICAL SPECIFICATIONS

- I Powers small camcorders with broadcast batteries
- I Powers up to 5 additional accessories (e.g. onboard light, monitor, external recorder, wireless audio, etc.)
- I 5 additional ports: 4 Hirose-4Pin 7.2 V and 12 V, 1 Twist-D-Tap
- I COCO-15 for 15 mm lightweight supports
- I COCO-AF for Panasonic AG-AF 100/101
- I Comfortably light only weighs approx. 0.3 kg



INTELLIGENT BATTERY 75 PLUS

FOR AUDIO AND SMALL CAMCORDERS

TECHNICAL SPECIFICATIONS

- I Dedicated to audio applications and small camcorders as the Sony PMW-F3 or the Panasonic AG-AF100/101
- I 5 additional outputs: 4 Hirose-4Pin 7.2 V and 12 V, 1 Twist-D-Tap
- I One main On/Off switch for all outputs

A75 plus	V 75 plus
14.8 V	14.8 V
4.4 Ah	4.4 Ah
4.8 A	4.8 A
0.64 kg	0.64 kg
89 x 175 x 48 mm	89 x 175 x 37 mm
2 hours	2 hours
	14.8 V 4.4 Ah 4.8 A 0.64 kg 89 x 175 x 48 mm

HIGH QUALITY LI-ION BATTERIES

TECHNICAL SPECIFICATIONS

- I Continuous load up to 7 A, 1-year cell warranty
- I Electronic control of over-voltage, under-voltage, over-current, over-charge, over-discharge and over-temperature
- I Compatible with different chargers (Sony, IDX, Anton Bauer, PAG, etc.)













WEIGHT

DIMENSIONS (WxHxD)

TYPE	A75	V75
VOLTAGE	14.8 V	14.8 V
CAPACITY	4.4 Ah	4.4 Ah
MAX. LOAD	4.8 A	4.8 A
WEIGHT	0.62 kg	0.62 kg
DIMENSIONS (WxHxD)	89 x 175 x 48 mm	89 x 175 x 37 mm
CHARGING TIME	2 hours	2 hours
TYPE	A 95	V 95
VOLTAGE	14.8 V	14.8 V
CAPACITY	6.6 Ah	6.6 Ah
MAX. LOAD	7.0 A	7.0 A
WEIGHT	0.88 kg	0.88 kg
DIMENSIONS (WxHxD)	89 x 175 x 57 mm	89 x 175 x 46 mm
CHARGING TIME	3 hours	3 hours
TYPE	A 140	V 140
VOLTAGE	14.8 V	14.8 V
CAPACITY	9.2 Ah	9.2 Ah
MAX. LOAD	7.0 A	7.0 A
WEIGHT	1.0 kg	1.0 kg
DIMENSIONS (WxHxD)	89 x 175 x 57 mm	89 x 175 x 46 mm
CHARGING TIME	4 hours	4 hours
TYPE	A 160	V 160
VOLTAGE	14.8 V	14.8 V
CAPACITY	11.0 Ah	11.0 Ah
MAX. LOAD	7.0 A	7.0 A
WEIGHT	1.3 kg	1.3 kg
DIMENSIONS (WxHxD)	89 x 175 x 75 mm	89 x 175 x 64 mm
CHARGING TIME	5 hours	5 hours
TYPE	A 190	V 190
VOLTAGE	14.8 V	14.8 V
CAPACITY	13.0 Ah	13.0 Ah
MAX. LOAD	7.0 A	7.0 A
WEIGHT	1.45 kg	1.45 kg
DIMENSIONS (WxHxD)	89 x 175 x 75 mm	89 x 175 x 64 mm
CHARGING TIME	6 hours	6 hours
TYPE	AS 2	VS 2
CHANNEL	2	2
MODE	simultaneous	simultaneous
AC ADAPTER	15V max 5A	15V max 5A

1.0 kg

135 x 230 x 100 mm

1.0 kg

135 x 230 x 100 mm





»I HAVE USED BEBOB V140RM
ONBOARD BATTERIES SINCE MID 2010
WITH THE BEST RESULTS. I SHOT WITH
AN ALEXA IN THE ALPS AT MINUS 10
DEGREES CENTIGRADE WITHOUT ANY
LOSS OF CAPACITY OR POWER ISSUE.«

ANDREAS BERKL, ARRI DIGITAL WORKFLOW SOLUTION

HIGH LOAD LI-MANGANESE BATTERIES

TECHNICAL SPECIFICATIONS

- I Continuous load of 12 A, Peak 15 A
- I 2-year cell warranty, 80 % capacity, with built-in alarm

A 90 RM

I Capacity display in percentage on ARRI ALEXA, RED ONE, Panasonic and Sony cameras

V 90 RM



TYPE





VOLTAGE	14.8 V	14.8 V
CAPACITY	6.0 Ah	6.0 Ah
MAX. LOAD	12 A	12 A
WEIGHT	1.0 kg	1.0 kg
DIMENSIONS (WxHxD)	89 x 175 x 57 mm	89 x 175 x 46 mm
CHARGING TIME	3 hours	3 hours
TYPE	A 140 RM	V 140 RM
VOLTAGE	14.8 V	14.8 V
CAPACITY	9.0 Ah	9.0 Ah
MAX. LOAD	12 A	12 A
WEIGHT	1.45 kg	1.45 kg
DIMENSIONS (WxHxD)	89 x 175 x 75 mm	89 x 175 x 64 mm
CHARGING TIME	4 hours	4 hours
TYPE	AS-2 RL	VS-2 RL
CHANNEL	2	2
MODE	simultaneous	simultaneous
AC ADAPTER	15 V max 5 A	15 V max 5 A
WEIGHT	1.0 kg	1.0 kg
DIMENSIONS (WxHxD)	135 x 230 x 100 mm	135 x 230 x 100 mm





HOT SWAP ADAPTER ML-120

AVAILABLE FOR ARRI ALEXA, RED ONE, SONY AND PANASONIC CAMCORDERS

TECHNICAL SPECIFICATIONS

- I The ML-120 allows you to swap the battery without interrupting camera powering
- I When the battery runs empty, ML-120 takes over the powering of the camera for 2 minutes while simultaneously providing a visible alarm
- I Features a 12 V DC D-Tap port, secured by a 5 A self-resetting fuse
- I After use, the ML-120 self-charges from the camera battery

TYPE (WITH V-MOUNT) ML-120 ML-120 ALEX ML-120V/V TYPE (WITH SNAP-ON) AML-120 AML-120 ALEX AML-120 A/A (on request CAPACITY 2 minutes 12 A 2 minutes 12 A 2 minutes 12 A MAX. LOAD 12 A 12 A 12 A WEIGHT 0.5 kg 0.62 kg 0.57 kg DIMENSIONS (W×H×D) 81 x 141 x 45 mm 81 x 141 x 55 mm 81 x 150 x 61 mm CHARGING automatic automatic automatic	FOR CAMERA	RED ONE	ARRI ALEXA	ALL CAMERAS
CAPACITY 2 minutes 12 A 2 minutes 12 A 2 minutes 12 A MAX. LOAD 12 A 12 A 12 A WEIGHT 0.5 kg 0.62 kg 0.57 kg DIMENSIONS (W×H×D) 81 x 141 x 45 mm 81 x 141 x 55 mm 81 x 150 x 61 mm	TYPE (WITH V-MOUNT)	ML-120	ML-120 ALEX	ML-120 V/V
MAX. LOAD 12 A 12 A 12 A WEIGHT 0.5 kg 0.62 kg 0.57 kg DIMENSIONS (W×H×D) 81 x 141 x 45 mm 81 x 141 x 55 mm 81 x 150 x 61 mm	TYPE (WITH SNAP-ON)	AML-120	AML-120 ALEX	AML-120A/A (on request)
WEIGHT 0.5 kg 0.62 kg 0.57 kg DIMENSIONS (W×H×D) 81 x 141 x 45 mm 81 x 141 x 55 mm 81 x 150 x 61 mm	CAPACITY	2 minutes 12 A	2 minutes 12 A	2 minutes 12 A
DIMENSIONS (W×H×D) 81 x 141 x 45 mm 81 x 141 x 55 mm 81 x 150 x 61 mm	MAX. LOAD	12 A	12 A	12 A
	WEIGHT	0.5 kg	0.62 kg	0.57 kg
CHARGING automatic automatic automatic	DIMENSIONS (WxHxD)	81 x 141 x 45 mm	81 x 141 x 55 mm	81 x 150 x 61 mm
	CHARGING	automatic	automatic	automatic



COMPANY PROFILE

Since 1995, bebob is an innovative partner of the film and broadcast production industry. The company offers three product ranges:

REMOTE Iris, focus and zoom controls for DSLR, Mini HD and

broadcast camcorders.

LIGHTING For ENG applications – onboard-, hand- and reporter lights from 4 to 60 W

employing tungsten and LED technology

POWER Broad range of batteries, chargers, accessories and Hot Swap adapters

based on two different technologies – Li-Ion and Li-Manganese.

bebob **designs, manufactures and assembles** in its headquarter in **Munich, Germany,** using the knowledge and traditional values of highly educated German craftsmanship.

bebob GmbH
Höglwörther Str. 350
81379 München
Tel. +49. 89. 27 81 82 82
Fax +49. 89. 27 81 82 81
www.bebob.tv