



▶ 75 mm ▶ (H)DV


# FSB 4

## Secure creativity

- Payload range: 0 – 4 kg / 0 – 9 lb
- Counterbalance: 5 steps +0
- 3 horizontal and 3 vertical grades of drag, +0
- Tilt range: +90° to –70°
- For tripods with 75 mm bowls, integrated flat base fitting

- Long sliding range of camera plate
- Robust, metal housing
- Damping components featured in the range of larger fluid heads
- Only available in system

MEASUREMENTS IN MM



# new!

CODE  
▶ 0307


- SYSTEMS
- ▶ Pages 72–79
  - SOOM FSB 4
  - FSB 4 SL MCF
  - FSB 4 / 2 MD
  - FSB 4 MD
  - FSB 4 / 2 D
  - FSB 4

PAYLOAD TABLE


C.O.G.*	min. kg/lb	max. kg/lb
50/2	0/0	3.9/8.5
75/3	0/0	3.2/7.0
100/4	0/0	2.7/5.9
125/5	0/0	2.3/5.1

\*Center of gravity height (mm/in)

PAYLOAD DIAGRAM



DAMPING



- ▶ Pages 72–79
- FSB 4 SL MCF PowerSet
- FSB 4 / 2 MD PowerSet
- FSB 4 MD PowerSet
- FSB 4 / 2 D PowerSet
- FSB 4 PowerSet



ACCESSORIES  
▶ Pages 64–71

