Panasonic

AK-UC3000 Series

4K Studio Handy Camera Scheduled for release in Winter 2015



4K studio camera system for broadcast-use supports 4K(UHD)/HD output and long-distance optical fiber transmission

The AK-UC3000 Series 4K Studio Handy Camera is a 4K broadcast-use camera equipped with a newly developed MOS sensor. When operated in HD format, it exhibits excellent operability with B4-mount HD lenses, achieving high sensitivity HD images (F10/2000 lx) with low noise (S/N 60 dB). While including functions appreciated in the conventional model such as DRS and CineGamma, the AK-UC3000 Series adds new features such as focus assist, flash band compensation, and skew reduction which is realized through high-speed scan from the MOS sensor. There are additional functions to improve shooting experience including enhanced shockless gain (-6 dB to 36 dB), a user gamma function, black gamma correction according to the pedestal setting, multi-step DNR and easy matrix adjustment.

AK-UC3000 Series achieves excellent image quality and operability. When used with AK-UCU500 Camera Control Unit, it is capable of 4K (3840x2160/60p) image output, high-image-quality uncompressed long-distance transmission and the AK-HRP1000/HRP1005 Remote Operation Panel equipped with a color LCD to provide visibility of the display for smooth control. The camera and camera control unit can be connected for approximately 2,000-meter long-distance transmission of video signals when power is supplied from the camera control unit. The remote operation panel and the camera can be connected using dedicated cable. In addition, there is a plan to support IP connection using LAN-cable. The AK-HVF100 9-inches (230 mm) LCD color view finder has also been newly developed equipped with a large display and diverse functions such as focus assist. Overall, this system offers superior cost performance with respect to both operability and ease of use.

4K Studio Handy Camera AK-UC3000 Series

AK-UC3000 (Tajimi connector model, LEMO connector model are available) 4K Studio Handy Camera (Scheduled for release in Winter 2015)

Newly Developed MOS Sensor Achieves



• Sensitivity F10 (2000 lx) and an excellent S/N ratio of 60 dB Supports 4K*1/HD acquisition.

- HD output from camera (3G-SDI): 1080/59.94p, 50p, 59.94i, 50i, 29.97PsF, 25PsF, 23.98p over 59.94i
- Equipped with a CAC (Chromatic Aberration Compensation) function capable of correcting even slight chromatic aberration at the lens periphery'
- The DRS (Dynamic Range Stretch) function suppresses blocked shadows and blown highlights*3
- The V-REC, F-REC provides powerful support in digital cinema production.
- Features an internal digital extender (x2 magnification)
- 12-axis color correction, detail, skin tone detail and easy matrix adjustment
- An SD Memory Card can be used for Set Up Data and firmware version up.
- IP streaming and IP control is supported*4. *1: 4K Output is available from AK-CUC500 via Optical Fiber Cable
- *2: When a CAC-compatible lens is used *3: Available with HD output via CCU only.
- *4: Future Support

AK-HRP1000 / HRP1005

Remote Operation Panel(ROP) (Scheduled for release in Winter 2015)

Compact Operation Panel Capable Of Supporting IP Control

• Available two types of Remote Operation Panel as 1/4 rack size

- AK-HRP1000 and 1/5 rack size AK-HRP1005.
- Easy recognition and visible LCD Panel AK-HRP1000: 3.5 inches (VGA)
- AK-HRP1005: 3.2 inches (VGA)
- Can be used for remote control of Panasonic convertible
- cameras and PTZ cameras*1
- · Equipped with a joystick control lever(Standard) Allows Iris/Pedestal operation
- Scene File function provided
- · Equipped with an SD Memory Card slot for saving user files and updating firmware version
- Supports IP Control (RJ45 LAN cable)
- *1: Future Support

Japan

AK-MSU1000

Master Setup Unit (MSU) (Scheduled for release in Winter 2015)

Maximum of 20 CCU can be connected and controlled from an AK-MSU1000 Support both IP and serial connection.

AK-UCU500 (Tajimi connector model, LEMO connector model are available) Camera Control Unit(CCU) (Scheduled for release in Winter 2015)

Allows a High-Quality, Long-Distance Optical Fiber

Transmission Camera System to Be Configured at Low Cost

- · Optical fiber transmission of uncompressed video signals over a distance of approximately 2,000 m between the camera and camera control unit*1
- The compact, lightweight unit measures 2U in height and is rack-mountable.
- Supported Format 4K (3G-SDI x 4) : 3840 x 2160/59.94p, 50p, 29.97p, 25p, 25PsF, 23.98p, 23.98PsF HD(3G-SDI) 1080/59.94p, 50p, 59.94i, 50i, 23.98p over 59.94i, 29.97PsF, 25PsF, 23.98PsF
 - 720/59.94p, 50p (3G-SDI x 4)*2: 1080/239.76p, 200p
- SD : 480/59.94i
- 576/50i
- Supports IP Streaming (RJ45 LAN Cable)
- An SD Memory Card can be used for saving user files and updating firmware version
- Input/Output: SDI OUT x 7, SDI OUT (PM) x 1, VBS x 1, VBS(PM) x 1
- *4K MODE :SDI OUT x 4(4K), SDI OUT x 3, SDI OUT (PM) x 1, VBS x 1, VBS(PM) x 1 *HS MODE*2: SDI OUT x 4(HS), SDI OUT x 3, SDI OUT (PM) x 1, VBS x 1, VBS(PM) x 1 RET input (SDI: 4ch, VBS: 1ch), HD-TRUNK output (SDI: 1ch), LAN-TRUNK output PROMPT input (SDI: 1ch, ANALOG: 2ch)

*1: When power is supplied from the camera control unit.

*2: HS is available when AK-HC5000 HD Studio Camerais connected.

AK-HVF100

22.9 cm (9 inches) LCD Color Viewfinder (Scheduled for release in Winter 2015)

Light Weight and High Resolution (Full HD) **Plus Versatile Assist Functions**

- Focus assist functions (Focus-in-Red, Focus Bar*1)
- Detail depends on Zoom Ratio*
- External HD-SDI Input
- Four assignable function switches
- Contrast, brightness and peaking are adjustable.

*1: Available when AK-HC5000 or AK-UC3000 are connected.

AK-HBU500

Build-up Unit (Scheduled for release in Winter 2015)

Supports Large, High-Power Lenses

• Power Output : DC12V / 9A, 1.5A



[Countries and Regions] Argentina

Australia

Panasonic Corporation AVC Networks Company 2-15 Matsuba-cho, Kadoma, Osaka 571-8503 http://pro-av.panasonic.net/

Bahrain	+973 252292
Brazil	+55 11 3889 4035
Canada	+1 905 624 5010
China	+86 10 6515 8828
Hong Kong	+852 2313 0888
Czech Republic:	+421 (0) 903 447 757
Denmark	+45 43 20 08 57
Egypt	+20 2 23938151
Finland, Latvia, Li	thuania, Estonia
	+358 (9) 521 52 53
France	+33 (0) 1 47 91 64 00
Germany, Austria	Switzerland
	+49 (0) 6103 313887
Greece	+30 210 96 92 300
Hungary	+36 (1) 382 60 60
India	+91 1860 425 1860
Indonesia	+65 6277 7284
Iran	
(Vida)	+98 21 2271463
(Panasonic Office)	+98 2188791102
Italy	+39 02 6788 367
Jordan	+962 6 5859801
Kazakhstan	+7 727 298 0891
Korea	+82 2 2106 6641
Kuwait	+96 522431385

+54 11 4122 7200 +61 (0) 2 9491 7400



Syria

+421 (0) 903 447 757 +27 11 3131622 +34 (93) 425 93 00 Sweden +46 (8) 680 26 41 +963 11 2318422/4 +886 2 2227 6214 Taiwan







Factories of AVC Networks Company have received ISO14001:2004-the Environmental Management Sv ent System certification. (Except for 3rd party's peripherals.)





- Serial control and IP control of studio cameras are possible.
- PoE (Power over Ethernet) supported