



P-V2 / P-VS2 V-Mount Camera Adaptor Plate

The P-V2 and P-VS2 are available to convert cameras without a rear V-Mount battery connection, so that any of the V-Mount ENDURA battery range can be easily attached. Both models are designed with multiple mounting holes to fit virtually all professional video cameras, with the added advantage of a built-in 50W DC output.

The P-VS2 is fitted with Synchron, a unique energy saving device that automatically turns an onboard camera light on and off in sync with the camera record button.

P-V2 / P-VS2 Product Features:

- **Multiple mounting holes** for universal camera connection
- **Digi-View data connectors** are fitted as standard on both models. Digital battery capacity data from the ENDURA ELITE, E-10 and E7 can be transferred through the P-V2 and P-VS2 to compatible view finder cameras. For accuracy and detail, remaining capacity is shown in steps of 1%.
- **Pre-wired power connectors** fitted as standard, eliminating the need for manual screw connection.
- **50W 2-pin D-Tap connector** uses battery voltage to power an onboard camera light or broadcast accessory.
- **Synchron** is a feature that allows an onboard camera light to be switched on and off in sync with the camera's record button, saving valuable energy and power for when it's most needed. Synchron is available on the P-VS2 only



P-V2



P-VS2

Technical Specification

Maximum Output for D-Tap:
50W

Dimensions:
82.5(W) x 142(H) x 12(D) mm

Weight:
P-V2 160g approx.
P-VS2 180g approx.

Included Accessories:
Installation manual x 1
M3 (8mm) screw x 4

E&OE

