

DP-V2410	
Display Unit	
Panel Type	IPS LCD panel
Screen Size	24-inch (61.1 cm)
Aspect Ratio	17:9
Resolution	4096x2160 pixels (8.8 megapixels)
Active Display Area	Approx. 540.7 x 285.1 mm
Pixel Pitch	132 µm
Panel Driver	1024 gradations 10-bit for each RGB colour
Brightness (Standard)	48 cd/m ² (DCI), 100 cd/m ²
Contrast ratio	2000:1 or greater
View Angle (Left:Right, Up:Down)	89° (contrast ratio 10 : 1 or higher)
Surface Treatment	Anti-glare
Backlight Type	RGB LED, Matrix array
Power	AC Power: 100V to 240V, 50/60 Hz DC Power: 24V (via XLR connector)
Power consumption	At maximum load: Approx. 210 W At factory shipment: Approx. 160 W
Environmental conditions	Operating: Range: 0 to 40 °C, 20 to 85% RH (no condensation) Recommended: 15 to 30 °C Storage/transporting: -20 to 40 °C, 10 to 85% RH (no condensation); 41 to 60 °C, 10 to 30% RH (no condensation)
Dimensions (width x height x depth)	Approx. 594 x 399 x 187 mm (with stand) Approx. 594 x 399 x 106mm (without protruding parts)
Weight	Approx. 12 kg
Mounting Hole Pitch	VESA* standard 100 x 100 mm
Input Interfaces	3G/HD-SDI: 4 (1 system), BNC (75Ω) HDMI: 1 (1 system), Type A (HDCP 2.2)
Output Interface	3G/HD-SDI: 4 (pass-through 1 system) Headphone: Stereo mini-jack
Control Interfaces	USB, 1 (USB 2.0 High Speed supported) LAN, 1 RJ-45 terminal
Supplied Accessories	AC Power Cord, Instruction Manual, Instruction Manual Disc
<p>*VESA are registered trademarks of Video Electronics Standards Association in the U.S and other countries. *Specifications and exterior are subject to change without notice.</p>	